





Compound placement may extend up to the cut edge at a given point but should not exceed .50 inch total length along the cut edge.

			В	-64	
Α	CURL DIAMETER	(in)	2.340 ± .010		
В	CURL HEIGHT	(in)	.081 ± .005		
С	INSIDE CURL DIAMETER	(in)	2.270 MIN		
D	COUNTERSINK DEPTH	(in)	.270 ± .005		
E	COMPOUND EDGE WIDTH	(in)	.040 ± .023		
F	COMPOUND BAND WIDTH	(in)	(in) .125 ± .035		
	COMPOUND WEIGHT			22 ± 5 mg	
			BEER	BEVERAGE	
	BUCKLE PRESSURE		92 psi min	90 psi min	
	POP	5 lb		MAX	
	PUSH	_	5.5 lbs MAX		

MATERIAL THICKNESS INFO					
UNCOATED	(in)	.0088 ± .0002			
BEVERAGE COATING	(in)	.0092 ± .0003			
BEER COATING	(in)	.0090 ± .0003			



METAL BEVERAGE CONTAINER OPERATIONS

9300 W. 108TH CIRCLE

WESTMINSTER, CO 80021-3682

P.O. BOX 589, BROOMFIELD, CO 80038-0589

T.U. DUA DBY, BRUOMFIELD, CO 80038-0589

THE DESIGNS, INFORMATION AND DATA CONTAINED HEREIN ARE PROPRIETARY AND ARE SUBMITTED IN CONFIDENCE, AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED IN WHOLE OR IN PART, FOR ANY PURPOSES WHATSOEVER WITHOUT THE PRIOR WRITTEN PERMISSION OF BALL CORPORATION. RECEIPT OF THIS DOCUMENT SHALL BE DEEMED TO BE AN ACCEPTANCE OF THE CONDITIONS SPECIFIED HEREIN.

202 B-64
BEER / BEVERAGE
.0088 GAUGE
MANUFACTURING SPECIFICATION

DATE CREATED APPROVED 8/21/14 D FRANK CREATED BY APPROVED ZANETELL J GORSUCH DATE REVISED

PRODUCT STANDARD

**END-253** 

9/14/15 С